O I P E JC68 JUN 22 2001 PATENT & TRADEMARK OFFICE

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of:		Atty. Docket No.:	03493.00156
Diakoumis P. Gerakoulis		(IDS 113351A)	
Serial No.:	09/770,858	Group Art Unit:	TBA
Filed:	January 26, 2001	Examiner:	TBA

RECEIVED JUN 25 2001 Technology Center 2600

For:
CDMA TO PACKET-SWITCHING INTERFACE FOR CODE DIVISION SWITCHING IN A TERRESTRIAL WIRELESS SYSTEM

REQUEST FOR APPROVAL OF DRAWING CHANGES

Commissioner for Patents
Washington, D.C. 20231

Sir:

The Examiner's approval is respectfully requested for the proposed changes to the drawings shown in red in the accompanying copy. Specifically, the proposed changes are as follows:

FIGS. 2-3b, 5c, 7b, 7f and 8c, change "❄" to --ω--.

FIGS. 3a-5a, change the word "acknowledgement" to acknowledgment.

FIG. 5a, (text box 2, line 1) add -- - -- between the words time and out.

FIG. 5a, (text box 2, line 3) delete . after the word acknowledgment.

FIG. 5a, (text box 2, line 6) add -- - -- between the words time and out and add --, -- after the word out.

FIG. 5a, (text box 3, line 5) add -- - -- re and use .

FIG. 5a, (text box 1) add -- 505 -- to the left, outside of text box.

FIG. 5a, (text box 2) add -- 510 -- to the left, outside of text box.

FIG. 5a, (text box 3) add -- 515 -- to the left, outside of text box.

FIG. 5c, (text box 2 line 2) add -- a space-- between the words microport and spreads.

FIG. 5c, (text box 2 line 4) add -- s -- at the end of the word transmit.

FIG. 5c, (text box 3, line 1) add -- - -- between the words time and out.

FIG. 5c, (text box 3, line 2) change the word "Received" to received.

FIG. 8b, change "W" to ω.

Respectfully submitted,

Dated: June 22, 2001

By: Catherine A. Ferguson

Catherine A. Ferguson
Registration No. 40,877

by Thomas H. Jackson
29,808

Banner & Witcoff, Ltd.
Eleventh Floor
1001 G Street, N.W.
Washington, D.C. 20001-4597
(202) 508-9100

THJ/CAF/dst



Fig. 1


MICROPORT
Paging Channel
(Forward Link)
(❄, f_d)
Contention Access Channel
(Reverse Link)
(g_j, f_u)
Orthogonal Data Traffic Channel
(Forward Link)
(❄, f_d)
Orthogonal Data Traffic Channel
(Reverse Link)
(❄, f_u)
MOBILE TERMINAL

Fig. 2


(g_j, f_u)
$(g_j, \#_i, f_u)$
P
H
payload data (ATM cells)
E
Time
acknowledgement received

Fig. 3a


(g_j, ❄_i, f_d)
(g_j, ❄_j, f_u)
PG
payload data (ATM cells)
E
Time
acknowledgement received

Fig. 3b


acknowledgement message
Microport
τ_p
payload data
(ATM cells)
Time
Mobile Terminal
τ_p
preamble & header
timing adjustment

Fig. 4a


acknowledgement message
Microport
τ_p
payload data
(ATM cells)
Time
Mobile Terminal
paging message

Fig. 4b


START
The mobile subscriber terminal transmits a preamble signal spread by a PN-code g_j (identifying the microport) and "marks" the point of the time origin. Following the preamble, a few bits of data are transmitted that identify the transmitting mobile user. This constitutes the packet header and is also spread by the PN-code g_j.
505
After an acknowledgement is received within time-out period, the mobile subscriber terminal spreads the information and data (i.e., ATM cell) by both the assigned orthogonal code (contained in the acknowledgement) and the PN-code. The mobile subscriber terminal also adjusts its transmission time (with respect to the marked point maintained by the microport) by the amount indicated in the acknowledgement so that all transmissions are synchronized. If no acknowledgement is received within time-out the mobile retransmits the preamble and header.
510
After the end of the information and data, the mobile subscriber terminal sends an end of packet flag, which is also spread by the orthogonal and PN codes. The assigned orthogonal code is released, making that unique code available for reuse.
515
END

Fig. 5a


START
540
Upon the arrival of one or more ATM cells at the transmitting microport, destined for a mobile user terminal, a paging message is sent to the mobile user terminal via the paging channel.
545
After an acknowledgement is received from the destination mobile user terminal, the transmitting microport spreads the payload data (extracted from the ATM cells) with the uniquely assigned orthogonal code and transmit the spread data to the destination mobile user terminal.
550
If, after a time-out period, no negative acknowledgment is received, the transmitting microport assumes correct reception of the data and releases the assigned (forward link) orthogonal code available for other transmissions.
END

Fig. 5c


START
555
While idle, the mobile user terminal monitors the paging channel for transmissions (paging messages).
560
If a paging message is received indicating the assignment of a particular orthogonal code, the mobile subscriber terminal switches to the orthogonal code assigned by the transmitting microport in order to receive the spread data. The destination mobile user terminal responds to the transmitting microport by sending an acknowledgment via the contention access channel.
565
After the "end of packet" flag is received, the mobile user terminal reverts to monitoring the paging channel for other paging messages (transmissions).
END

Fig.5d


CAI
Originating mobile subscriber terminal
Receiving microport
Core Network
CAI
Transmitting microport
Destination mobile subscriber terminal

Fig. 6


Transmitter of the subscriber terminal i
FEC
Spreader
Modulator
RF
Receiver - 1
Receiver - i
PN-code Acquisition Process
Demod
Data Despreader
Decoder
Receiver - N
N Receivers in Microport j

Fig. 7a


Spreader
Preamble & Header Transmission
(Contention Access)
Payload Data Transmission
(Contention-Free Access)
1
2
Modulator
RF
$\mathbf{\ast}_i$
g_j

Fig. 7b


720
Array of Parallel SSDCs
725
BBF
A/D
cos 2πf_u t
730
l-parallel data receivers
1
Channel Receiver/Decoder
2
735-a
Channel Receiver/Decoder
π/2
sin 2πf_u t
735-b
l
Channel Receiver/Decoder
BBF
A/D
735-l

Fig. 7c


720
DEMOD
SSDC-0
725-a
SSDC-1
725-b
SSDC-k
725-k
SSDC-K
725-K
730
l-parallel
Data
Detectors

Fig. 7d


A.
Demodulator
$\sum_1^{\gamma_i}$
$(\cdot)^2$
$\sum_1^{\gamma_i}$
$(\cdot)^2$
Σ
$\gtrless\Theta_i$
Decision Logic
YES
NO
set i = 1 or 2
Access Channel PN - code Generator
(k-1)w < n ≤ kw
n ← n + 1
update phase
by $\Delta T_c = 1/2$
B.
Start Search
Update Phase $\Delta T_c = 1/2$
miss
$\sum_1^{\gamma_1}$ (search)
Hit
miss
$\sum_1^{\gamma_2}$ (Verification)
Hit
Fine Synch.

Figure 7e



Fig. 7f


FEC
Spreader
Modulator
RF
Demodulator
Despreader
Decoder
Transmitting microport
Destination mobile subscriber (user) terminal

Fig. 8a



Fig. 8b



Fig. 8c